



A Guide for Estimating the Remaining Unused PC Strand Length¹ (in Feet) in a Standard Reel- less Center-Pull Pack

# Layers ²	3/8" 250K	3/8" 270K	7/16" 250K	7/16" 270K	1/2" 250K	1/2" 270K	1/2" HBS	9/16" 270K	0.6" 270K	0.62" 270K
30	24,210									
29	23,801									
28	22,766	22,145								
27	21,746	21,792								
26	20,742	20,784								
25	19,753	19,792	17,595							
24	18,780	18,815	17,148	16,150						
23	17,821	17,854	16,257	15,891						
22	16,878	16,908	15,380	15,031						
21	15,951	15,978	14,519	14,186	12,695	12,375	11,930			
20	15,038	15,063	13,673	13,356	12,211	11,967	11,469	10,515		
19	14,141	14,163	12,843	12,542	11,453	11,223	10,751	10,256		
18	13,259	13,279	12,028	11,744	10,711	10,493	10,048	9,578	8,845	8,300
17	12,393	12,410	11,229	10,961	9,985	9,780	9,361	8,916	8,452	8,263
16	11,541	11,557	10,445	10,193	9,274	9,081	8,688	8,269	7,832	7,654
15	10,705	10,719	9,677	9,440	8,578	8,398	8,031	7,637	7,228	7,060
14	9,885	9,896	8,923	8,703	7,898	7,731	7,389	7,021	6,639	6,482
13	9,079	9,089	8,186	7,982	7,234	7,078	6,763	6,420	6,066	5,920
12	8,289	8,298	7,464	7,275	6,585	6,441	6,151	5,834	5,507	5,372
11	7,514	7,521	6,757	6,584	5,951	5,820	5,555	5,263	4,964	4,840
10	6,755	6,761	6,065	5,909	5,333	5,214	4,974	4,708	4,436	4,323
9	6,010	6,015	5,389	5,249	4,730	4,623	4,408	4,169	3,924	3,822
8	5,281	5,285	4,729	4,604	4,142	4,048	3,857	3,644	3,427	3,336
7	4,568	4,570	4,084	3,975	3,570	3,488	3,322	3,135	2,945	2,865
6	3,869	3,871	3,454	3,361	3,014	2,944	2,802	2,641	2,478	2,410
5	3,186	3,188	2,840	2,762	2,473	2,414	2,297	2,163	2,027	1,970
4	2,518	2,519	2,241	2,179	1,948	1,901	1,807	1,699	1,591	1,545
3	1,866	1,866	1,658	1,611	1,437	1,403	1,332	1,252	1,170	1,136
2	1,229	1,229	1,090	1,059	943	920	873	819	765	742
1	607	607	537	522	464	452	429	402	375	363

¹The lengths shown are estimates and are not intended to be used to calculate exact lengths.

²From the ID.

NOOR-National Office of Raw Materials of Pre-stressing Systems, LLC.

Headquarter Office:
1133 Broadway, Manhattan, Suite 706,
New York, NY10010 .USA
Tel: +1 (212) 631 5819
Fax: +1 (212) 631 5820
www.noorprestressing.com

Australia:
88 Phillip St, Sydney, NSW 2000,
Fax: +6 (128) 0886 195
mtest@noorps.com
tsupport@noorps.com
www.noorps.com

